

Trade name: einZA mix Korral-Top, Basis 4**Product no.:** 0078200**Current version :** 4.1.0, issued: 03.01.2024**Replaced version:** 4.0.0, issued: 25.10.2022**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name

einZA mix Korral-Top, Basis 4**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**
decorative paints/finishes**Uses advised against**
No data available.**1.3 Details of the supplier of the safety data sheet****Address**einZA Farben GmbH & Co KG
Junkersstraße 13
30179 HannoverTelephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einZA.com**Advice on Safety Data Sheet**

sdb_info@umco.de

1.4 Emergency telephone numberFor medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**Aquatic Chronic 2; H411
Flam. Liq. 3; H226
STOT SE 3; H336**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07



GHS09

Signal word

Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statement(s)H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Trade name: einZA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

H411	Toxic to aquatic life with long lasting effects.
Hazard statements (EU)	
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statement(s)	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	64742-48-9 919-857-5 - 01-2119463258-33	Asp. Tox. 1; H304 EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00	wt%
2	trizinc bis(orthophosphate)			
	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 5.00 - < 10.00	wt%
3	(2-METHOXYMETHYLETHOXY)PROPANOL			
	34590-94-8 252-104-2 - 01-2119450011-60	-	< 2.50	wt%
4	n-butyl acetate			
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 2.50	wt%
5	potassium 2-ethylhexanoate			
	3164-85-0 221-625-7 607-230-00-6 01-2119980714-29	Eye Dam. 1; H318 Repr. 2; H361d Skin Irrit. 2; H315	< 0.50	wt%
6	zinc oxide			

Trade name: einZA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 0.25	wt%
--	--	--------	-----

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
6	-	-	M = 1	M = 1

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Trade name: einZA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	(2-METHOXYMETHYLETHOXY)PROPANOL	34590-94-8	252-104-2
	2000/39/EC		
	(2-Methoxymethylethoxy)-propanol		
	WEL long-term (8-hr TWA reference period)	308	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	(2-Methoxymethylethoxy) propanol		
	WEL long-term (8-hr TWA reference period)	308	mg/m ³ 50 ppm
	Comments	Sk	

Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

2	n-butyl acetate	123-86-4	204-658-1
List of approved workplace exposure limits (WELs) / EH40			
Butyl acetate			
	WEL short-term (15 min reference period)	966 mg/m ³	200 ppm
	WEL long-term (8-hr TWA reference period)	724 mg/m ³	150 ppm
EU 2019/1831			
n-Butyl acetate			
	WEL short-term (15 min reference period)	723 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	241 mg/m ³	50 ppm

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			64742-48-9 919-857-5
	dermal	Long term (chronic)	systemic	77 mg/kg/day
	inhalative	Long term (chronic)	systemic	871 mg/m ³
2	n-butyl acetate			123-86-4 204-658-1
	dermal	Long term (chronic)	systemic	11 mg/kg/day
	dermal	Short term (acut)	systemic	11 mg/kg/day
	inhalative	Long term (chronic)	systemic	300 mg/m ³
	inhalative	Short term (acut)	systemic	600 mg/m ³
	inhalative	Long term (chronic)	local	300 mg/m ³
	inhalative	Short term (acut)	local	600 mg/m ³
3	potassium 2-ethylhexanoate			3164-85-0 221-625-7
	dermal	Long term (chronic)	systemic	5.95 mg/kg/day
	inhalative	Long term (chronic)	systemic	41.98 mg/m ³
4	zinc oxide			1314-13-2 215-222-5
	dermal	Long term (chronic)	systemic	83 mg/kg/day
	with reference to: Zn Comments: insoluble			
	inhalative	Long term (chronic)	systemic	5 mg/m ³
	with reference to: Zn Comments: insoluble			
	inhalative	Long term (chronic)	local	0.5 mg/m ³
	with reference to: Zn Comments: insoluble			

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			64742-48-9 919-857-5
	oral	Long term (chronic)	systemic	46 mg/kg/day
	dermal	Long term (chronic)	systemic	46 mg/kg/day
	inhalative	Long term (chronic)	systemic	185 mg/m ³
2	n-butyl acetate			123-86-4 204-658-1
	oral	Long term (chronic)	systemic	2 mg/kg/day
	oral	Short term (acut)	systemic	2 mg/kg/day
	dermal	Long term (chronic)	systemic	6 mg/kg/day
	dermal	Short term (acut)	systemic	6 mg/kg/day
	inhalative	Long term (chronic)	systemic	35.7 mg/m ³
	inhalative	Short term (acut)	systemic	300 mg/m ³
	inhalative	Long term (chronic)	local	35.7 mg/m ³
	inhalative	Short term (acut)	local	300 mg/m ³

EU safety data sheet



Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

3	potassium 2-ethylhexanoate			3164-85-0	
				221-625-7	
	oral	Long term (chronic)	systemic	2.98	mg/kg/day
4	zinc oxide			1314-13-2	
				215-222-5	
	oral	Long term (chronic)	systemic	0.83	mg/kg/day
	with reference to: Zn Comments: insoluble				
	dermal	Long term (chronic)	systemic	83	mg/kg/day
	with reference to: Zn Comments: insoluble				
	inhalative	Long term (chronic)	systemic	2.5	mg/m ³
	with reference to: Zn Comments: insoluble				

PNEC values

No	Substance name	CAS / EC no	
	ecological compartment	Type	Value
1	trizinc bis(orthophosphate)		7779-90-0
			231-944-3
	water	fresh water	20.6 µg/L
	water	marine water	6.1 µg/L
	water	fresh water sediment	117.8 mg/kg dry weight
	water	marine water sediment	56.5 mg/kg dry weight
	water	fresh water	85 µg/L
	water	marine water	42.5 µg/L
	water	fresh water sediment	867.4 mg/kg dry weight
	water	marine water sediment	957.7 mg/kg dry weight
	soil	-	35.6 mg/kg
	sewage treatment plant	-	100 µg/L
	2	n-butyl acetate	
		204-658-1	
water		fresh water	0.18 mg/L
water		marine water	0.018 mg/L
water		Aqua intermittent	0.36 mg/L
water		fresh water sediment	0.981 mg/kg dry weight
water		marine water sediment	0.0981 mg/kg dry weight
soil		-	0.0903 mg/kg
sewage treatment plant	-	35.6 mg/L	
3	potassium 2-ethylhexanoate		3164-85-0
			221-625-7
	water	fresh water	0.36 mg/L
	water	Aqua intermittent	0.493 mg/L
	water	fresh water sediment	0.637 mg/kg dry weight
	water	marine water sediment	0.637 mg/kg dry weight
	water	marine water	0.036 mg/L
soil	-	1.06 mg/kg dry weight	
4	zinc oxide		1314-13-2
			215-222-5
	water	fresh water	20.6 µg/L
	with reference to: Zn		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

water	marine water	6.1	µg/L
with reference to: Zn			
water	fresh water sediment	117.8	mg/kg
water	marine water sediment	56.5	mg/kg
with reference to: Zn, dry weight			
soil	-	35.6	mg/kg
with reference to: Zn, dry weight			
sewage treatment plant	-	100	µg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	liquid
Form	liquid
Colour	according to product name
Odour	like solvents
pH value	No data available
Boiling point / boiling range	

Trade name: einZA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Value	>	120	°C
Reference substance	solvent mixture		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	>=	30	°C
Method	closed cup		
Ignition temperature			
Value	>	200	°C
Reference substance	solvent mixture		
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0.6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7.5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	appr.	1.36	g/cm ³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow			2.3
Reference temperature			25 °C
Method		OECD 117	
Source		ECHA	
Kinematic viscosity			
Value	2100 - 2300	mPa*s	
Reference temperature	20	°C	
Method	DIN 53019		
Solvent separation test			
Value	<	3	%

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Reference temperature	20 °C
-----------------------	-------

Particle characteristics

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
4	zinc oxide	1314-13-2	215-222-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Source	ECHA
2 n-butyl acetate	123-86-4 204-658-1
LD50	> 14112 mg/kg bodyweight
Species	rabbit
Method	OECD 402
Source	ECHA
3 zinc oxide	1314-13-2 215-222-5
LD50	> 2000 mg/kg bodyweight
Species	rat
Method	OECD 402
Source	ECHA

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LC50	>	5.41	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
2	zinc oxide	1314-13-2	215-222-5
LC50	>	5.7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
3	n-butyl acetate	123-86-4	204-658-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
4	zinc oxide	1314-13-2	215-222-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species	rabbit		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Method	OECD 405
Source	ECHA
Evaluation	non-irritant
3	n-butyl acetate 123-86-4 204-658-1
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	non-irritant
4	zinc oxide 1314-13-2 215-222-5
Species	rabbit
Method	OECD 405
Source	ECHA
Evaluation	non-irritant

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Route of exposure		Skin	
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
2	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Route of exposure		Skin	
Species	guinea pig		
Source	ECHA / Read across		
Evaluation	non-sensitizing		
3	zinc oxide	1314-13-2	215-222-5
Route of exposure		respiratory tract	
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure		Skin	
Species	Guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Route of exposure		inhalational	
NOAEC		500	ppm
Duration of exposure		90	day(s)

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Species	rat
Method	EPA OTS 798.2450
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
LL50	>	1000	mg/l
Duration of exposure		96	h
Species	Rainbow trout		
Method	OECD 203		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
EL50	>	1000	mg/l
Duration of exposure		48	h
Species with reference to	Daphnia magna		
Method	WAF (water accommodated fractions)		
Method	OECD 202		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species with reference to	Daphnia magna		
Method	CAS 110-19-0		
Source	OECD 211		
Evaluation/classification	ECHA		
	Based on available data, the classification criteria are not met.		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
EL50		>	1000 mg/l
Duration of exposure		72	h
Species with reference to	Pseudokirchneriella subcapitata		
Method	WAF (water accommodated fractions)		
Source	OECD 201		
	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		
Half-life		3.3	day(s)
Reference temperature		25	°C
Source	ECHA		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.

Trade name: einza mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

1	n-butyl acetate	123-86-4	204-658-1
BCF			15.3
Method	Calculation model used (Q)SAR		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263

Trade name: einzA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

Proper shipping name	PAINT
Technical name	trizinc bis(orthophosphate)
EmS	F-E+S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-ethylhexanoic acid	149-57-5	205-743-6	75
2	potassium 2-ethylhexanoate	3164-85-0	221-625-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5c

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 28.87 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : i, type: lb = 500 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

Trade name: einZA mix Korral-Top, Basis 4

Product no.: 0078200

Current version : 4.1.0, issued: 03.01.2024

Replaced version: 4.0.0, issued: 25.10.2022

Region: GB

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 772632