

Trade name: einZA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

coating material

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG
Junkersstraße 13
30179 Hannover

Telephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einZA.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product does not meet the classification and labelling criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Not relevant

2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	benzyl alcohol			
	100-51-6 202-859-9 603-057-00-5 01-2119492630-38	Acute Tox. 4; H302 Acute Tox. 4; H332	< 2.50	wt%
2	propylidynetrimethanol			
	77-99-6 201-074-9 - -	Repr. 2; H361fd	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
1	1230 mg/kg bodyweight		

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack**Product no.:** 0072698**Current version :** 4.0.0, issued: 28.02.2022**Replaced version:** 3.0.0, issued: 08.11.2021**Region:** GB**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	benzyl alcohol			100-51-6 202-859-9	
	dermal	Long term (chronic)	systemic	8	mg/kg/day
	dermal	Short term (acut)	systemic	40	mg/kg/day
	inhalative	Long term (chronic)	systemic	22	mg/m ³
	inhalative	Short term (acut)	systemic	110	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	benzyl alcohol			100-51-6 202-859-9	
	oral	Long term (chronic)	systemic	4	mg/kg/day
	oral	Short term (acut)	systemic	20	mg/kg/day
	dermal	Long term (chronic)	systemic	4	mg/kg/day
	dermal	Long term (chronic)	systemic	20	mg/kg/day
	inhalative	Long term (chronic)	systemic	5.4	mg/m ³
	inhalative	Short term (acut)	systemic	27	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	benzyl alcohol		100-51-6 202-859-9	
	water	fresh water	1	mg/L
	water	marine water	0.1	mg/L
	water	Aqua intermittent	2.3	mg/L
	water	fresh water sediment	5.27	mg/kg dry weight
	water	marine water sediment	0.527	mg/kg dry weight
	soil	-	0.456	mg/kg dry weight
	sewage treatment plant	-	39	mg/L

8.2 Exposure controls**Appropriate engineering controls**

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	>=	0.7	mm
Appropriate Material	nitrile rubber		
Material thickness	>=	0.4	mm

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form/Colour			
Liquid			
Various, depending on coloration			
Odour			
uncharacteristic			
pH value			
No data available			
Boiling point / boiling range			
Value		301	°C
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	>	100	°C
Ignition temperature			
Value		420	°C
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
No data available.			
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value		1.52	g/cm ³
Reference temperature		20	°C
Solubility in water			

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

Comments	difficult to mix		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
log Pow		1.05	
Reference temperature		20	°C
Source	ECHA		
Viscosity			
Value	5000	mPa*s	
Reference temperature	20	°C	
Type	dynamic		
Solvent separation test			
Not applicable			
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack		
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).		
Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LD50		1230	mg/kg bodyweight
Species	rat		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LD50		2000	mg/kg bodyweight
Species	rabbit		
Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack		
Comments	The result of the applied calculation method according to the European		

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

		Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).	
Acute inhalational toxicity			
No data available			
Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Species	Salmonella typhimurium TA98, TA100, TA1535, TA1537		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Reproduction toxicity			
No data available			
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Route of exposure	oral		
		400	mg/kg bw/d
Species	rat		
Method	OECD 451		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
Aspiration hazard			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.			

11.2 Information on other hazards

Endocrine disrupting properties

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
LC50		460	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA OPP 72-1		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
EC50		230	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
NOEC		51	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
EC50		710	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
IC50		390	mg/l
Duration of exposure		24	h
Species	Nitrosomonas sp.		
Method	ISO 8192		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
Value		92	- 96 %
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	benzyl alcohol	100-51-6	202-859-9
log Pow		1.05	
Reference temperature		20	°C

Trade name: einzA LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

Source	ECHA
--------	------

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances
 The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.
 Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)
According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.
REACH candidate list of substances of very high concern (SVHC) for authorisation
According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.
Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET

Trade name: einza LawiPen 2-K-PU Beschichtung, RAL 7035 Stammlack

Product no.: 0072698

Current version : 4.0.0, issued: 28.02.2022

Replaced version: 3.0.0, issued: 08.11.2021

Region: GB

AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES	
According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances subject to restriction as listed in Annex XVII of the REACH regulation (EC) 1907/2006.	
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances	
This product is not subject to Part 1 or 2 of Annex I.	
Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)	
VOC content	1.4 %

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.
 The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.
 Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.
 National Threshold Limit Values of the corresponding countries as amended in each case.
 Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H302	Harmful if swallowed.
H332	Harmful if inhaled.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

Creation of the safety data sheet

UMCO GmbH
 Georg-Wilhelm-Str. 187, D-21107 Hamburg
 Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.
 The safety data sheet describes products with a view to safety requirements.
 It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:
 Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
 Prod-ID 672855